

EC DECLARATION OF CONFORMITY (in accordance with BS EN ISO/IEC 17050-1:2010

No. 2011-11-05

FUTURE GARMENTS LTD, AQUA HOUSE, BUTTRESS WAY, SMETHWICK, WARLEY, WEST MIDLANDS B66 3DL

We hereby declare that the following Personal Protective Equipment :

JK269-000-287 - Flame Retardant Welders Split Leather / FR Cotton Jacket

Are in conformity with the provisions of Council Directive 89/686/EEC and with the national transposing harmonized Standard No's :

EN ISO 11611 : 2007, EN ISO 11612 : 2008 and is identical to the PPE which is the subject of EC Type Certificate No: LECF100322336 dated 23rd November 2011 issued by the : (Notified Body No : 0362)

ITS Testing Services (UK) Ltd , Centre Court , Meridian Business Park , Leicester , LE19 1WD , UK

Signed for and on behalf of :

Name : H.S.Uppa

Name : Max Palak

Position : Technical Director

Position : Managing Director

Date: 23rd November 2011

Place of issue : Birmingham , Head Office.

	Intertek			ITS Testing Services (UK) Ltd., Centre Court, Meridian Business Park, Leidester LE19 1WD, UK Bnited Kingdom Tel: 44 (0)119/263 0330	
			EC TYPE EXAMINATION CERTIFICAT	TE Approved Body 036	
	Issued to	:	Future Garments Ltd., Aqua House, Bu Birmingham. B66 3DL	ttress Way, Smethwick,	
	Manufacturer	:	Future Garments (India) Pvt Lto., March 75010, India	neswar Ind. Est., Bhubaneswar,	
	Date of Issue	:		iry Date : 21 st July 2016	5
	Certificate No.	:	LEC FI00322336 (Extension to Certificat		
	Product Reference	:	Flame Retardant Welders Split Leathe - JK269 000-287	er/FR Cotton Jacket	
	Description	:	Weiners Jacket in compliance with EN Front Class 2 A1, Back Class 1 A1 Must be worn with Trousers to at leas		
JEP	The welders jacket	detailed	above meets the criteria of an EC type E	Contraction intercontinue with	
	article 10 of the PPI This has been show	E Directi n through	ve (89/686/EEC) for intermediate design	category products.	
	technical file docum Following an EC de	claratior	of product conformity, you are hereby in with article 13 of the PPE Directive (89	censed to mark the product(s)	
		2	Assessor	Date: 23 rd November 2011	
	Jøyce videre	abr		Date: 23 rd November 2011	
	Carol Graham	laxi Bro	WT C		
	For and on behalf of ITS Testing Services ITS Testing Services (UK) I				
L	ITS Testing Services (UK) I Registered in England No. 3287320 R	egistered Offi	e: 25 Savile Road London W1S 2ES		
	2				



PRODUCT DATA SHEET

Leather and FR fabric welders jacket

Product Code: JK269





FEATURES AND BENEFITS:

Lightweight leather and FR fabric Heavy duty side split leather chest & sleeves Full velcro fastening front Suitable for MIG and TIG welding Full Kevlar stitching throughout Fabric back keeps you cool

Full Description:

RHINOweld lightweight leather & FR fabric, welders jacket, designed for maximum comfort and safety. Heavy duty side split leather chest and sleeves provide superior protection for both Mig & Tig welding. KEVLAR stitched. The flame retardant cloth back offers ultimate levels of comfort and keeps you cool even in humid conditions.

For spatter protection, the flip up high collar is secured by velcro which enhances the full velcro overlay to the front.

Technical Data:

CE CE approved to EN ISO11611:2007 Class 2 A1 Welding standards front, Class 1 A1 back of garment

High collar for maximum spatter protection Velcro fastening to collar

XSML	SML	MED	LRG	EXL	XXL	3XL	4XL	5XL	6XL	7XL
	•		•	•		•				

USER INFORMATION

Leather & FR Cotton Welding Jacket - JK269

These garments comply with the requirements of Directive 89/686/EEC and the referenced standards	DESCRIPTION: JACKET - TAN SPLIT LEATHER FRONT & BLACK FR COTTON BACK			
EN ISO 11611:2007 Protective Clothing for use in Welding and Allied Processes	EN ISO 11611 : 2007 Front Class 2 A1 Back Class 1 A1 Intended Use: Class 1 – recommended for manual welding techniques with light formation of Spatters and drops e.g. gas welding, TIG			
withdraw and carefully remove garments, ensuring the chemical or liquid do not come into contact with any part of skin. Clothing should be cleaned or removed from service.	welding, MIG welding, micro plasma welding, brazing, spot welding, MIMA welding (with rutile covered electrode) for operation of machine e.g. oxygen cutting machines, plasma cutting machines, resistance welding machines, machines for thermal spraying, bench welding			
Improper use. The level of protection against flame will be reduced if the welders' protective clothing is contaminated with flammable materials. An increase in the oxygen content of the air will reduce considerably the protection of the welder's protective clothing against flame. Care should e.g. taken when welding in confined spaces e.g. if it is possible that the atmosphere may become enriched with oxygen. The electrical insulation provided by clothing will be reduced when the clothing is wet, dirty or soaked with sweat. For two-piece protective clothing, both items must be worn together to provide the specified level of protection. Any other warnings, regarding limitations of use, as identified by the manufacturer. Cleaning & Maintenance; The items of PPE described and marked with the appropriate style / product codes are not designed to be Washed, Laundered or Cleaned in any manner. Notified Body : Intertek Labtest UK Ltd	thermal spraying, bench welding Class 2 – recommended for manual welding techniques with heavy formation of spatters and drops e.g. MIMA welding (with basic or cellulose-covered electrode), MAG welding (with CO ₂ or mixed gases), MID welding (with high current), self-shielded flux cored arc welding, plasma cutting, gouging, oxygen cutting, thermal spraying for operation of machines e.g. in confined spaces, at overhead welding/cutting or in comparable constrained positions This clothing is intended to protect against flames molten metal splatter, radiant heat and short term, accidental electrical contact Warnings: For operational reasons not all welding voltages carrying parts of arc welding installations can be protected against direct contact. Additional partial body protection may be required e.g. for welding overhead. This gament is only intended to protect against brief inadvertent contact with live parts of an arc welding circuit, additional electrical insulations layers will be required where there is an increased risk of electric shock,. Garments are designed to provide protection against short term, accidental contact with live electric conductors at voltages up to approximately 100 V.d.c. Garments should fastened and worn correctly for protection. When using additional partial protective garments, the basic garments shall meet at least 1. Storage: Always store in clean, dry conditions. Disposal: Products for recycling, safe destruction and disposal as relevant with local regulations			
Notified Body : Intertek Labtest UK Ltd Centre Court, Meridian Business Park, Leicester , LE19 1WD, UK Notified Body No.0362	Future Garments Ltd Aqua House , Buttress Way , Smethwick Birmingham , B66 3DL , UK www.workwearonline.net			

The information contained herein is intended to assist the wearer in the selection of Personal Protective Equipment. The results of physical tests should also help in glove selection, however it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the user to determine the suitability of the glove for its intended use.